



American Portable
AIR & POWER

CPTH-12 1TON HEAT PUMP

Specifications

Cooling Capacity Btu/hr 11,500
Operating Range: Min-MaxF° 65°-95°
Heating Capacity Btu/hr 10,300
Operating Range: Min-MaxF° 40°-80°
Ion Total Positive/Negative Ion Output >350M ions/cc/sec

Dimensions:

Width(Inches) 19
Depth(Inches) 26.5
Height(Inches) 41.7
Weight (Pounds) 165

Electrical Power Supply (Volts) 115
Current Consumption (Amps) 11.5
Fuse Size (Amps) 15
Plug Configuration 5-15
Voltage (Min-Max) 105-125
Power Cord Length (Feet) 8
Fan Evaporator: Air Flow (CFM) High/Low 470/400
Condenser: Air Flow (CFM) High/Low 1005/888
Compressor Type Rotary
Refrigerant Type R-32

Safety Devices:

Compressor Overcurrent Protection
Fan Motor Protection
Anti-Freeze Thermostat
Fan Mode Switch
Automatic Restart
Automatic Tank ShutOff
Audible Condensate ShutOff Alarm
Built In Safety Switch for Condensate Pump
Condensate Tank Capacity(Gal) 4.9
LED Control Panel with Timer
UL2998 Certified Ozone Free
CARB Certified
UL 60335-2-40 Certified



www.AmericanPortableAir.com

877-823-2722